



SOCA45EXTB

Serve Over Counter

Product Features

- Black finish
- Ventilated cooling
- Anti mist front glass
- Multiplexing kit as accessory
- LED top light
- Stainless steel bumper bars
- Excellent product visibility
- Glass front lifts up for easy cleaning
- Stainless steel rear shelf

45° corner module for serve over counter

This SOCA corner module is designed for creating complete counter solutions in combination with other serve over counters from the same range. If you need a 90° rounded corner, it is also possible to combine two of these 45° corner modules. This specific model is wide out towards the customer and more narrow towards the staff side. We also offer a model with the opposite dimensions, depending on which way you would like your counter to turn.

This high-quality serve over counter offers a sleek design featuring anti-mist glass, LED top lighting, and a spacious stainless steel deck that stays chilled thanks to ventilated cooling and airholes on the backside of the deck. It's ideal for butcher shops and delis looking for gorgeous display space. In addition to it's good looks, it's also practical and easy to clean with a stainless steel interior and front glass that lift upwards and stays in place while cleaning. Be aware that if the corner module is installed along with another SOC counter, you cannot open the front glass on both units at the same time or you risk ruining the glass.

Measures and Content

Total Display Area	m²	0.88
Temperature Range	°C	0 to +4
Climate Class		3
Net Volume	l	90
Gross / Net Volume	l	/ 90
Gross / Net Weight	kg	200 / 160

Design and Material

Feet / Legs	Adjustable feet
Interior Light	LED
Exterior Finish	Black RAL9005
Interior Finish	Stainless Steel

Cooling and Functions

Type of Controller	Electronic
Type of Cooling	Ventilated
Type of Defrost	Automatic, electric
Refrigerant	R290
Refrigerant Charge	g130
Thermometer	Yes

Power and Consumption

Max Ambient		+25°C, 60% RH
Annual Energy Cons.	kWh/year	1445.4
Energy Consumption	kWh/24h	3.96
Input Power	W	610
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

Dimensions

External Dimension (WxDxH)	mm	x 1120 x 1190
Internal Dimension (WxDxH)	mm	x 900 x 545
Packed Dimension (WxDxH)	mm	1400 x 1250 x 1400
40ft Container Load	pcs	8



Digital controller



Bumper bars