



DB201S

Backbar Cooler

Product Features

- Approx. 56% more energy efficient than previous range
- Double glazed tempered glass
- Energy saving variable speed compressor
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- Adjustable shelves
- LED interior light

Energy-efficient backbar cooler

This new range of DB backbars is highly energy efficient and uses in average 56% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. The temperature is easily adjusted on the electronic thermostat.

The backbar cooler has self-closing sliding doors with double glazed tempered glass, which gives a nice product presentation. The adjustable wire shelves have a white plastic coating for easy maintenance. The backbar is ideal for busy bar environments, and with its black exterior and stucco aluminium interior it has a contemporary look. A great choice for any bar.

The DB range is also available in a variant with hinged doors.

Measures and Content

Gross / Net Weight	kg	69 / 63
Net Volume	l	182
Gross Volume	l	190
Gross / Net Volume	l	190 / 182
Total Display Area	m²	0.47
Temperature Range	°C	+2 to +10
Climate Class		4

Design and Material

Exterior Finish	Black RAL9005	
Interior Finish	Stucco aluminium	
No. of Doors	2	
Door No & Type	2 sliding glass doors	
Door Reversible	No	
No. of Shelves	pcs	4
Shelves No & Type	4 wire shelves white	
Shelf Color	White	
Shelf Dimensions	395x320 mm	
Max load on Shelves	kg/m²	196
Feet / Legs	4 adjustable feet	
Lock	Yes	
Interior Light	LED	
Tempered glass	Yes	

Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic	
Refrigerant Charge	g	70
Refrigerant	R600a	
Thermometer	Yes	

Power and Consumption

Display cabinet family	VC4	
Energy Class	A	
Annual Energy Cons.	kWh/year	416
Energy Consumption	kWh/24h	1.14
EEL	%	9
Input Power	W	115
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	44

Dimensions

External Dimension (WxDxH)	mm	900 x 550 x 870
Internal Dimension (WxDxH)	mm	810 x 418 x 720
Packed Dimension (WxDxH)	mm	985 x 575 x 940
40ft Container Load	pcs	96



Protective thermostat
cover



Door holder for loading of
the cabinet