



DB202S

Backbar Cooler

Product Features

- Double glazed tempered glass
- Ventilated cooling for fast pull-down and even temperature
- LED interior light
- Adjustable wire shelves
- Easy access electronic thermostat
- Automatic defrost
- Adjustable feet
- Lock

Backbar with sliding doors

Keep your bar running smoothly with a competitively priced backbar cooler built for busy bars, restaurants, and cafés. It has a black exterior and anthracite interior for a modern look, while LED lighting highlights the beverages on display. Adjustable wire shelves can be organized to fit cans or tall bottles, and the plastic coating makes life easier for the staff who has to keep the backbar clean.

Ventilated cooling pulls the temperature down fast after a restock and keeps the temperature even from corner to corner, so you can keep up with customer demand. An easy-access electronic thermostat lets staff set and check temperatures with confidence.

Simple to use, easy to clean, and ready for daily service – this backbar cooler helps your team serve faster and sell more.

Measures and Content

Gross / Net Weight	kg	69 / 63
Net Volume	l	187
Gross Volume	l	220.5
Gross / Net Volume	l	220.5 / 187
Total Display Area	m²	0.23
Temperature Range	°C	+2 to +10
Climate Class		4

Design and Material

Exterior Finish		Black RAL9005
Interior Finish		Grey RAL7037
No. of Doors		2
Door No & Type		2 sliding glass doors
Door Reversible		No
No. of Shelves	pcs	4
Shelves No & Type		4 wire shelves grey
Shelf Color		Grey
Shelf Dimensions		395x320 mm
Max load on Shelves	kg/m²	230
Feet / Legs		4 adjustable feet
Lock		Yes
Interior Light		LED
Tempered glass		Yes

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant Charge	g	40
Refrigerant		R600a
Thermometer		Yes

Power and Consumption

Type of refrigeration		Beverage cooler
Energy Class		D
Annual Energy Cons.	kWh/year	500.42
Energy Consumption	kWh/h	0.057
Energy Consumption	kWh/24h	1.371
EEl	%	39.5
Input Power	W	152.2
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45

Dimensions

External Dimension (WxDxH)	mm	900 x 526 x 870
Internal Dimension (WxDxH)	mm	810 x 418 x 720
Packed Dimension (WxDxH)	mm	985 x 575 x 940
40ft Container Load	pcs	96



Protective thermostat
cover



Lock